



12CA5

12CA5

BEAM POWER TUBE

MINIATURE TYPE

Intended for use in equipment having
series heater-string arrangement

GENERAL DATA

Electrical:

Heater, for Unipotential Cathode:

Voltage.	12.6	ac or dc volts
Current.	0.6	amp
Warm-up time (Average)	11	sec

For definition of heater warm-up time and method of determining it, see sheet HEATER WARM-UP TIME MEASUREMENT at front of this Section.


Direct Interelectrode Capacitances (Approx.):^o

Grid No.1 to plate	0.5	μmf
Grid No.1 to cathode & grid No.3, grid No.2, and heater.	15	μmf
Plate to cathode & grid No.3, grid No.2, and heater.	9	μmf

Mechanical:

Mounting Position.	Any
Maximum Overall Length	2-5/8"
Maximum Seated Length.	2-3/8"
Length, Base Seat to Bulb Top (Excluding tip).	2" \pm 3/32"
Maximum Diameter	3/4"
Bulb	T-5-1/2
Base	Small-Button Miniature 7-Pin (JETEC No.E7-1)
Basing Designation for BOTTOM VIEW	7CV

Pin 1-Cathode,
Grid No.3
Pin 2-Grid No.1
Pin 3-Heater



Pin 4-Heater
Pin 5-Grid No.1
Pin 6-Grid No.2
Pin 7-Plate

AMPLIFIER - Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE.	130 max.	volts
GRID-No.2 (SCREEN) VOLTAGE	130 max.	volts
GRID-No.1 (CONTROL-GRID) VOLTAGE:		
Positive bias value.	0 max.	volts
PLATE DISSIPATION.	5 max.	watts
GRID-No.2 INPUT.	1.4 max.	watts
PEAK HEATER-CATHODE VOLTAGE:		
Heater negative with respect to cathode.	200 max.	volts
Heater positive with respect to cathode.	200 [▲] max.	volts
BULB TEMPERATURE (At hottest point on bulb surface)		
	180 max.	^o C

^o without external shield.

[▲] The dc component must not exceed 100 volts.

MAR. 1, 1955

TUBE DIVISION

TENTATIVE DATA

RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

12CA5



12CA5

BEAM POWER TUBE

Typical Operation and Characteristics:

Plate Voltage.	110	125	volts
Grid-No.2 Voltage.	110	125	volts
Grid-No.1 Voltage.	-4	-4.5	volts
Peak AF Grid-No.1 Voltage.	4	4.5	volts
Zero-Signal Plate Current.	32	37	ma
Max.-Signal Plate Current.	31	36	ma
Zero-Signal Grid-No.2 Current.	3.5	4	ma
Max.-Signal Grid-No.2 Current.	7.5	11	ma
Plate Resistance (Approx.)	16000	15000	ohms
Transconductance	8100	9200	μ mhos
Load Resistance.	3500	4500	ohms
Total Harmonic Distortion.	5	6	%
Max.-Signal Power Output	1.1	1.5	watts

Maximum Circuit Values:

Grid-No.1-Circuit Resistance:

For fixed-bias operation	0.1 max. megohm
For cathode-bias operation	0.5 max. megohm

MAR. 1, 1955

TUBE DIVISION

TENTATIVE DATA


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY



12CA5

12CA5

AVERAGE PLATE CHARACTERISTICS



JAN. 24, 1955

TUBE DIVISION

92CM-8507


RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

12CA5



12CA5

OPERATION CHARACTERISTICS



JAN. 20, 1955

TUBE DIVISION
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

92CM-8506R1